



- Decorative brass lever on 53mm diameter brass round rosettes.
- Concealed fixing.
- Passage sets available. Purchase two dummy kits (KT700A DFP) to convert a passage set into two dummy levers.
- Non-handed to suit left or right-handed doors.
- For use with 1000, 3000, 755 or 655 series mortice locks for exterior doors or with 480 or 960/980 series tubular latches for interior doors.
- Suits one 35mm and two 6mm diameter holes through door face when used with a 480 or 960/980 series tubular latch.
- For doors 35mm to 45mm thick.



Moda lever on round rosette
9414 CP SC

Auxiliary Privacy Set

- Normally installed above passage leverset to add privacy locking to internal doors.
- Complements the 9400 series levers.
- Incorporates privacy bolt, internal tumbbutton escutcheon and external emergency release escutcheon.
- Concealed fixing.
- Suits a 22mm diameter hole through door face.
- For doors 35mm to 45mm thick.
- 60mm backset.



Privacy set
94PS CP SC

Cylinder, Turnbutton and Emergency Release Escutcheons

- Range of round cylinder, tumbbutton and emergency release escutcheons (all 53mm diameter except oval which is 50mm).
- Coordinates with the 9400 series levers when used in conjunction with mortice locks.
- Concealed fixing.



Oval cylinder escutcheon*
to suit 1000 or 3000 series mortice locks
10E3 CP SC



Interior tumbbutton escutcheon
10T3 CP SC



Euro profile cylinder escutcheon*
to suit 755 or 655 series mortice locks
10EU3 CP SC



Emergency release escutcheon
10R3 CP SC

When ordering, add relevant finish code to form complete catalogue number, as shown under products illustrated.

* Denotes cylinder purchased separately.

316 Grade Stainless Steel for Higher Corrosion Resistance

- Fashionable lever designs with concealed fixing.
- Non-handed to suit left or right-handed doors.
- Corrosion resistant. Tested to 960 hours.*
- For use with 1000, 3000, 755 or 655 series mortice locks for exterior doors and with 480 or 960/980 series tubular latches for interior doors.
- Suits one 35mm and two 6mm diameter holes through door face when used with a 480 or 960/980 series tubular latch.

Note: A 50mm diameter hole is required when used with a 9609 privacy adaptor.

- For doors 35mm to 45mm thick.**
- Can be used on fire doors.

Tubular 316 Grade Stainless Steel Levers – Economical tubular design options.



Metax lever on round rosette
9421 SS



Asgard lever on round rosette
9424 SS

Privacy Adaptor

- 9609 Privacy adaptor will suit 9400 series stainless steel range. Refer to page 15 for further details.



Privacy adaptor with Nautilus lever
9609 SSF

Solid 316 Grade Stainless Steel Levers – Premium quality design options.



Ariel lever on round rosette
9420 SS



Nautilus lever on round rosette
9422 SS



Clipper lever on round rosette
9423 SS



Taeping lever on round rosette
9425 SS



Lynx lever on round rosette
9426 SS



Peloris lever on round rosette
9427 SS



Applicable to 9400 Series Leversets only, not applicable to Privacy Adaptor.



When ordering, add relevant finish code to form complete catalogue number, as shown under products illustrated.

* Denotes Gainsborough Salt spray test.

** Denotes longer screws available (FAMT124) to suit 50mm thick doors.

(continued overleaf)



Auxiliary Privacy Set

- Normally installed above passage leverset to add privacy locking to internal doors.
- 55mm diameter rosettes to complement the 9400 series levers.
- Incorporates privacy bolt, internal turnbutton escutcheon and external emergency release escutcheon.
- Escutcheons are 316 grade stainless steel. Tested to 960 hours.*
- Concealed fixing.
- Suits a 25mm diameter hole through door face.
- For doors 35mm to 45mm thick.
- 60mm backset.

NEW



Auxiliary privacy set
96PS SS

Note: Faceplate and strike plate are finished in Satin Chrome



Inset shows external emergency release escutcheon on reverse

Sliding Bolt Set

- Suits sliding doors.
- 55mm diameter rosettes to complement the 9400 series stainless steel levers.
- Incorporates latch, internal turnbutton escutcheon and emergency release escutcheon. (No indicator.)
- Escutcheons are 316 grade stainless steel. Tested to 960 hours.*
- Concealed fixing.
- Suits a 35mm diameter hole through door face.
- For doors 35mm to 45mm thick.
- 60mm backset.
- Not able to be recessed into sliding door pocket.

NEW



Sliding bolt set
96SB SS

Note: Faceplate and strike plate are finished in Satin Chrome



Inset shows external emergency release escutcheon on reverse



Applicable to Key Escutcheons only; not applicable to Auxiliary Privacy Set or Sliding Bolt Set.

Round Cylinder, Turnbutton and Emergency Release Escutcheons

- 316 grade stainless steel; concealed fixing.
- Coordinates with the 9400 series levers when used in conjunction with 1000 or 3000 series mortice locks.
- 55mm diameter x 12mm thick.
- Corrosion resistant. Tested to 960 hours.*



Oval cylinder escutcheon** to suit 1000 or 3000 series mortice locks
10E4 SS



Euro cylinder escutcheon**
10EU4 SS



External oval cylinder escutcheon** used with 10T4 or 10E4 Through fixing for
– Double cylinder function
– Single cylinder and turnbutton function
10E4E SS



Interior turnbutton escutcheon
10T4 SS



Emergency release escutcheon
10R4 SS

When ordering, add relevant finish code to form complete catalogue number, as shown under products illustrated.

* Denotes Gainsborough Salt spray test.

** Denotes cylinder purchased separately.

480 and 960/980 Series Dual Sprung Tubular Latches

- Gainsborough tubular latches feature a heavy duty main spring for firm action and positive return during normal operation.
- Secondary latchbolt spring for easy door closure.
- Choose from delrin or steel hubs.
- 'D' or universal 'T' strikes available – refer specific catalogue number.
- Requires a 35mm diameter hole through door face and a 25mm diameter hole through door edge.



Rectangular face and strike
60mm backset
480 BC FB **PB** SC (481 70mm backset)



Rectangular face and universal strike
60mm backset
480T BC PB SC



Rectangular face and universal strike
features sintered steel cam
60mm backset, Heavy duty
980 CP PB* SC



Radius corner face and strike
60mm backset
488 BC PB

ES1000 Electric Strike



Applicable to Electric Strikes only;
not applicable to 480 and 960/980
Series Dual Sprung Tubular Latches.

- The ES1000 Electric Strikes are designed for use with deadlatching mortice locks having up to 12mm throw latchbolt.
- The ES1000 Electric Strikes are available in un-monitored and monitored 12 volt or 24 volt DC for use on aluminium or timber frames.
- Power to lock (fail safe) or power to open (fail secure), can be changed on site by simply changing position of a screw.



Electric strike
ES1000/12 SS
ES1000/12M SS (Monitored)
ES1000/24 SS
ES1000/24M SS (Monitored)

When ordering, add relevant finish code to form complete catalogue number, as shown under products illustrated.

* For this finish, order 960PB until stock depleted. On depletion, the 980PB will become available.